# ADDENDUM No. 2 TO THE CONTRACT DOCUMENTS

**Project:** Captain's Bay 35kV Line Extension

Addendum Issue Date: May 11, 2017

Issued for Bid Date: April 14, 2017

**Bid Due Date:** May 16, 2017, 2:00pm (AK)

Previous Addenda Issued: Addendum No. 1, April 27, 2017

**Issued By:** William Farrell

Electric Power Systems, Inc. 3305 Arctic Blvd., Suite 201 Anchorage, Alaska 99503

\_\_\_\_\_\_

#### **Notice to Bidders:**

Bidders must acknowledge receipt of this addendum prior to the date set for bid opening by one of the following methods:

(1) By acknowledging receipt of this addendum on the bid submitted.

(2) By fax which includes a reference to the project and addendum number.

The bid documents require acknowledgment individually of all addenda to the drawings and/or specifications. This is a mandatory requirement and any bid received without acknowledgment of receipt of addenda may be classified as not being a responsive bid. If, by virtue of this addendum it is desired to modify a bid already submitted, such modification may be made by fax provided such a fax makes reference to this addendum and is received prior to the opening date specified above.

The contract Documents for the above project are amended as follows (all other terms and conditions remain unchanged):

# ITEM 1

Contract: City of Unalaska Captain's Bay 35kV Line Extension

Section: Project Drawings

The attached drawing E1.14 has been added to the plans set in order to provide further detailed information regarding existing utilities located at and around the Westward Seafoods Captain's Bay facility. Facilities in this area are owned by Westward, North Pacific Fuel and the City of Unalaska. Requirements for obtaining locates are not changed.

Note that this increases the sheet count to 31 drawings. Page numbers on existing drawings should all now read Sheet X of 31 rather than Sheet X of 30. However, this drawing update will not be modified prior to bid opening.

### ITEM 2

Contract: City of Unalaska Captain's Bay 35kV Line Extension

Section: Project Drawings

The attached PDF photos are from a recent excavation at the Westward facility. These photos are a visual aide and representation of the site utilities in the vicinity of the Westward Powerhouse at the time the photos were taken. They are provided for informational purposes only for interpretation by the Contractor.

The PDF documents are Fish Oil Line at Westward (Attachment #2, 11 pages), Misc. Utilities at Westward (Attachment #3, 42 pages) and Westward 4160 Volt (Attachment #4, 41 pages)

## ITEM 3

Contract: City of Unalaska Captain's Bay 35kV Line Extension

Section: Project Drawings and Bid Tab

The following bidder question and corresponding answer was provided by email on May 4, 2017.

Bidder Question:

Please confirm the description for the requested cables. The description you provided calls for a 1/3 neutral. The Okonite Part Number you provided (135-23-3656) is an MV-105 Cable with a copper tape shield.

#### Answer

The 35kV cable description on the bid tab is correct. The revised Okonite Part Number for a 1/0 AL 1/3 concentric cable with 133% insulation (420 mils) is 160-23-7072. The drawing reference to 345 mils on Sheet E1.03 is incorrect and is to be 420 mils.

## ITEM 4

Contract: City of Unalaska Captain's Bay 35kV Line Extension

Section: Part 10 Geotechnical/As-built


The PDF drawing set titled Petro Star, Inc. Westward Seafoods Fuel Upgrade As-Built (10 pages) is provided for informational purposes only for interpretation by the Contractor.

END OF ADDENDUM

City of Unalaska Captains Bay 35kV Line Extension Project Addendum No. 2

Attachment 1

"Drawing E1.14"



City of Unalaska Captains Bay 35kV Line Extension Project Addendum No. 2

Attachment 2

"Fish Oil Line at Westward"























City of Unalaska Captains Bay 35kV Line Extension Project Addendum No. 2

Attachment 3

"Misc. Utilities at Westward"





















































































City of Unalaska Captains Bay 35kV Line Extension Project Addendum No. 2

Attachment 4

"Westward 4160 Volt"



















































































#### Attachment 5

"Petro Star, Inc. Westward Seafoods Fuel Upgrade As-Built"

AS-BUILT RECORD 11/24/00

# PETRO STAR, INC. WESTWARD SEAFOODS FUEL UPGRADE AT UNALASKA, ALASKA



CONTRACTOR: MAC COULTER

INDUSTRIAL & COMMERCIAL CONSTRUCTION

ENGINEER: MARK ROCKWELL, P.E.
ROCKWELL ENGINEERING & CONSTRUCTION

	DRAWING INDEX
DWG. No.	TITLE
0	COVER SHEET
1	FUEL PIPELINE ROUTING PLAN
2	FUEL PIPELINE BURIAL DETAILS AND GENERAL NOTES
3	DOCK LAYOUT PLAN AND SECTIONS
4	FUEL STATION PLAN AND DETAILS
5	TANK CONTAINMENT PLAN
M1	MECHANICAL SITE PLAN, FLOOR PLAN AND DETAILS
М2	MECHANICAL SPECIFICATIONS
E1	ELECTRICAL SITE PLAN AND DETAILS
E2	ELECTRICAL SPECS, POWER PLAN AND DETAILS

Peratrovich, Nottingham & Drage, Inc.

Engineering Consultants

1506 West 36th Avenue, Anchorage, Alaska 99503

19071 581-1011

Peratrovich, Nottingham, and Drage, Inc. (PN&D) is not responsible for safety pragrams, methods or procedures of operation, or the construction of the design shawn on these drawings. Drawings are for the use of this project only and are not intended for reuse without written approval from PN&D. Drawings are also not to be used in any manner that would constitute a detriment directly or indirectly to PN&D.

SHERN O

# PETRO STAR INC. WESTWARD SEAFOODS FUEL UPGRADE



Peratrovich, Nottingham & Drage, Inc.

Engineering Consultants

1506 West 36th Avenue Anchorage, Alaska 995


(907) 561-1011

FAX (907) 563-422


0ate: 3/22/00 Scale: AS SHOWN

COVER SHEET

0 . 5




### FUEL LINES OVERCROSSING WATER LINE TYPICAL DETAIL



- 1. MEASUREMENTS ARE FROM OUTSIDE DIA. OF PIPE.
- 2. TRENCH SIDE SLOPE WILL VARY W/ MATERIAL AND DEPTH.
- 3. CONTACT WESTWARD SEAFOODS, INC. AND PETRO STAR, INC. PRIOR TO ANY EXCAVATION.

## TYPICAL PIPELINE TRENCH DETAIL



FUEL LINES UNDERCROSSING WATER LINE TYPICAL DETAIL

#### GENERAL NOTES

#### DATUM

TOAL LEVELS - ELEVATION DATUM FOR THIS PROJECT IS Q O MEAN LOWER LOW WATER

TOAL LEVELS FROM PORT OF UNALASKA

EXTREME HICH WATER
MEAN HICHER HICH WATER (WHHW)
MEAN HICH WATER (MHW)
MEAN LOW WATER (MLW) +6.6 FT. +3.7 FT. +3.4 FT. +1.2 FT. +0.0 FT MEAN LOWER LOW WATER (MLLW) EXTREME LOW WATER

#### MATERIALS

ALL STEEL PIPE USED FOR FUEL LINES SHALL BE ASTM ASS GRADE B. ALL PIPING IS OWNER SUPPLIED

MOPE PIPE SLEEVE-ALL FUEL LINE CROSSING OF WATER LINES AND LOCATIONS WHERE FUEL LINES ARE WITHIN 10 FEET HORIZONTALLY OF A WATER LINE SHALL BE SLEEVED WITH SDR 21 HOPE PIPE AS SHOWN IN THE DRAWINGS.

PPMC & CONDUT SUPPORT-UNCER DOCK PIPING SUPPORTS SHALL BE 12 GAUCE UNISTRUT P2544, GALVANIZED, OR ENGINEER APPROVED EQUAL.

FASTEMERS-ALL NUTS, BOLTS, WASHERS, SCREWS, AND CLAMPS SHALL BE GALVANIZED.

PIPE BEDDING-PIPE BEDDING SHALL CONFORM TO THE FOLLOWING CRADING REQUIREMENTS:

E PASSING BY WEIGHT SIEVE DESIGNATION 3-INCH 1-INCH #40 100 30-70 0-10

#### INSTALLATION

4.

STRUCTURAL STEEL WELDING-PIPE SUPPORT WELDING SHALL BE PER LATEST AWS DI.1 BY WELDERS QUALIFIED PER AWS FOR THE TYPE AND POSITION AS NEEDED.

POST-BURIAL EARTHWORK SHALL LEAVE THE SITE IN PRE-CONSTRUCTION CONCITION ALL BACKFILL SHALL BE GRADED SO THAT IT IS SMOOTH AND FLUSH IN THE ADJACENT EXISTING GROUND CONTOURS.

SUBMITTALS—
CERTIFICATIONS, MANUFACTURER'S DATA, AND OTHER INFORMATION FOR ALL MATERIALS, INCLUDING THOSE NOT SPECFICALLY NOTED IN THE CENERAL NOTES OR SHOWN ON INDIVIDUAL DRAWNOS, SHALL BE SUBMITTED TO THE ENGINEER FOR WRITTEN APPROVAL. ALL METHODS AND MATERIALS SHALL CONFORM TO THE CONTRACT DOCUMENTS, CENERAL NOTES, THE PLANS, GOOD WORKMANSHIP, CENERALLY ACCEPTED INDUSTRY STANDARDS, AND MANUFACTURER'S RECOMMENDATIONS.

THE FOLLOWING IS A LIST OF REQUIRED SUBMITTALS FOR THIS PROJECT:

1. AWS WELDING CERTIFICATION FOR ALL WELDERS UTILIZED ON THIS PROJECT

1:1

- 2. PROPOSED WELDING PROCEDURES
- 3 HOPE PIPE 4 REDLINED AS-BUILT DRAWNGS

## CAUTIONII

THE LOCATIONS OF EXISTING UTILITIES SHOWN ON THIS DRAWING ARE APPROXIMATE. THERE MAY ALSO BE ADDITIONAL UTILITIES THAT ARE NOT SHOWN, IT IS THE CONTRACTOR'S RESPONSIBILITY TO FIELD LOCATE ALL EXISTING UTILITIES PRIOR TO BECINNING EXCAVATION.

WATER AND WASTEWATER TELEPHONE AND CABLE TV POWER & LICHT

(907) 581-1260 (907) 581-1398 (907) 581-1260

AS BUILT 11/24/00

Peratrovich, Nottingham, and Drage, Inc. (PN&D) is not responsible for safety programs, methods or procedures of operation, or the construction of the design shown on these drawings. Drawings are for the use of this project only and are not intended for reuse without written approval from PN&D. Drawings are also not to be used in any monner that would constitute a detriment directly or indirectly to PN&D.

## PETRO STAR INC. WESTWARD SEAFOODS FUEL UPGRADE

\_ EF

p Peratrovich, Nottingham & Drage, Inc.

Engineering Consultants

1506 West 36th Avenue Anchorage, Alaska 99503

(907) 561-1011

FAX (907) 563-4220

3/22/00 Date: NOTED Scale:


Project No: 99067


Checked: Approved: ABC


> FUEL PIPELINE BURIAL **DETAILS & GENERAL NOTES**


2 . 5

Designed:









#### PART I CEMERAL

- 1.1 PROJECT RECORD DRAWINGS
- in matter recovery proximities of Division I, more up a clean set of drawings as the sort progresses to show the dimensioned location and routing of of mechanical and which will become permanently conceiled. Show routing of work in conceiled blind spaces within the bridley.
- 8. Show the location of all waters and their appropriate tog identification
- 12 MANUFACTURER'S DIRECTIONS
- A All mishulloctured orticles shall be applied, installed and handled as recommended by the mishulacturer, unless specifically called out otherwise in the pions. Advise the Engineer of any such conflicts before installation.
- A. The Contractor shall arrange for a permit from the local authority. The Contractor shall pay for any inspection fees or other fees and charges required by ordinance, law, codes and these specifications.
- A The Contractor shall, at his own expenses, perform the various tests as specified and required by the Architect and as required by applicable code, the State, and

#### PART 2 PRODUCTS

- 2.1 MATERIALS
- At equipment shall be regularly cotaloged items of the manufacturer and shall be supplied as a complete unit in accordance with the manufacturer's standard specifications along with any optional items required for proper installation unless otherwise noted. Maintain manufacturer's identification, model number, etc. on all an installation of the time of the contracturer's identification, model number, etc. on all an installations.
- 2.11 EARTHQUAKE RESTRAINTS
- A. Secure lone to structure to prevent movement during seismic disturbance in UBC

#### PART J DECUTION

- 3.1 INSTALLATION
- A. All work shall comply with the latest adopted applicable codes and ordinances including, but not limited to, the UMC, UPC, UBC, NPPA and UFC Standards; all local and state amendments to all codes and standards.
- A Before the facility is turned over to the Owner, instruct the Owner or Owner's personned in the operation, care and mointercace of all systems and expirement. These instructions shall also be included in a critten summary in the Operating and Mointenance Monutas.
- 3.3 OPERATING AND MUNTENINGE MUNUALS
- Submit operating and maintenance manuals to the Owner covering all equipment installed by the Contractor.
- B. The operation and maintenance manuals shall be bound in a loose leaf binder with reinforced holes in the shoets so as to prevent lost pages. The manual shall contain, but not limited to, the following types of information:
- 1. Cololog cuts of all equipment firtures, etc installed (Norhed to identify the
- 1. Lorolog cuts or an equipment innume, and associate including specific items used).
  2. Harunocturar's mointenance and overhout instruction booklets including exploded views.
  3. Identification numbers of all parts and nearest source for obtaining parts and
- 4. Reduced scale drawings of the control system and a verbal description of how these controls operate.

  6. A copy of volve schedule and reduced scole drawings showing volve locations.

  7. Written surrouny of instructions to Owner.
- C. A periodic maintenance form that includes all of the equipment shall be provided with the maintenance manual. The form shall list each piece of equipment and how often maintenance is required (daily, eventy, monthly, annually). Opposite each task shall be squares for check-oils for a full year (nitials) to verify that the tasks.

#### J. A IDENTIFICATION

- A Tog oil volves with heat resistant laminated plastic labels or brass tags engraved with readily legible letters. Securely tasten to the valve stem or bonnet with beaded chain. Provide a framed, howevitten directory under glass, and installed where directed. Provide complete record drawings that show all valves with their
- B. Label all equipment with heat resistant laminated plastic labels having engraved lettering 1/2" high. If items are not specifically listed on the schedules, consult the Engineer concerning designation to use.
- C. Identify piping to indicate contents and flow direction of each pipe exposed to view by a labeled sliceve in letters readable from floor at least once in each room and at intervals of not more that 20° apart.
- A Unless otherwise indicated, mount oil equipment and install in accordance with manufacturer's recommendations and approved submittals. Where equipment is to be anchored to structure, furnish and locate necessary anchoring and vibration
- 3.7 PIPE HANCERS AND SUPPORTS
- A. Support all piping independent of connected equipment.

SECTION 15484 - FUEL SYSTEMS

PART I GENERAL

1.1 SEE SECTION 15050 - BASIC MATERIALS AND METHODS

PART 2 PROCUCTS

- 2.1 FUEL FIFTHS, ABOVE GRADE
- A Sinel Pipe: Provide some material and weight as exterior piping except bare pipe, no protective coating. See Civil drawings for pipe requirements. Joints: Welded
- 2.2 BUTTERFLY VALVES
- A. Duchle from eith upper and lower bushings, bug style, for NASI 150 Ronges, 200 PSI rated, aluminum bronze disc, Buna-N liner, 416 stainless steel stem, with lever handle and locking natched throtting plate.
- 2.3 STRANER
- A Fisher-Rosemount Petroleum, in line strainer
- 2.4 FUEL TRANSFER PUMP
- A. Cormon-Rupp, model RSJA11-B, self priming centrifugal pump, electric motor driven. 7.5 HP, 270 CPM at 50 ft. hd.
- 2.5 PIPELINE EXPANSION RELIEF VILVE
- A. Nortison Series 77 exponsion relief volve. All bross construction for copper tube littings. 40 PSI setting.
- 2.6 PRESSURE CAUCE
- A 4-1/2 inch cost oluminum case, phosphor branze bourban tube, rotary branze movement, brase socket, with siticone fluid dampening, black figures on white background, one percent mid-scale occuracy, 0-60 PSIC range. Trainice Model 600C.
  B. Provide Johnst Mini 1-82-bit lever handle ball type isolation valve. Provide pulsation damper Coince 870 to Trainic.

#### PART J EXECUTION

- 3.1 INSTALLATION PIPING
- A install piping to conserve building space and not interfere with use of space.

  B. Inetall piping to allow for expansion and contraction without stressing pipe, joints, or connected equipment.

- or connected equipment.

  C. Provide clearance for access to volves and filtings.

  D. Test poing to 100 PSIC for four hours with no noticeable pressure drop.

  E. Install volves with acutuators and handles upright or horizontal. Do not install
- J.2 INSTALLATION PUMPS

9:6:

- A. Install in accordance with manufacture's recommendations.

  B. Provide base as required to properly support and secure the pump.

  C. Maintain manufacture's recommended minimum clearances.

AS BUILT 11/24/00



# PETRO STAR INC. WESTWARD SEAFOODS FUEL UPGRADE

Peratrovich, Nottingham 3 Drage, Inc.

1508 Beet 30th Avenue, Anchoraga, Aleska 99603 (907) 881-1011 FAX (907) 563-4220

Designed: LFH MWB Checked:

Date:

LFH Approved Project No. 99205

03/13/00


RSA Engineering, Inc.

MECHANICAL SPECIFICATIONS

n Engineering Consultants


M2 2

AS BUILT 11/24/00




#### NOTES:

- CONNECT TO NEW SOLUP CROUT BREWER IN EISTING 120/2004, PANELBOARD IN EDSTING POWER HOUSE BUILDING, COORDMATE WITH OWNER FOR LOCATION, RUN IN TRENICH ALONG ROAD WITH FUEL PIPPING, COOPDMATE WITH OWNER ON LOCATION TO RUN TRENICH ACROSS ROAD.
- PROVIDE NEW 1°C IN TRENCH WITH FUEL PIPING FROM PUMP HOUSE TO DOOK FOR PUMP CONTROLS. SEE 2/E1
  FOR TRENCH DETAIL.
- 3. CONNECT TO FUEL PUMP MOTOR STARTER IN PUMP HOUSE WITH 2/10 IN 1°C.
- 4. PULL BOX, SEE 3/EI
- 5. PROVICE NEW STEEL, ZINC-PLAIRED CROUNCING REEL WITH 50' INTLON COATED CARLE (DAMEL MODDHEAD \$14305) OR APPROVED EQUAL), COCHONATE WITH OWNER FOR CABLE CLAMP TIPE TO PROVIDE TO BE COMPATIBLE WITH SHIP FLYELING CROUNCING CONNECTION, MOUNT ON HEN DECK AS REQUIRED, PROVIDE \$2 BARE CU CROUND CONNECTION TO EXISTING CROUND AT DOCK STEEL PLANCS AND TO CROUND CONNECTION AT FLYEL DISPENSER.
- 6. SEE 3/E2 FOR PUMP HOUSE PLAN.




1.1



	LEGEND
8	COMBINATION DISCONNECT/MACHETIC BIGTOR STARTER
8	MOTOR (SIZED AS NOTED)
	CONDUT, CONCENED
11.10	MUMBER AND SIZE OF WIRES (NO WHRES - 3 /12)
~	HOMERUM TO PANEL
c	соноит
	NOTE TAG (No. INCICATES NOTE)





# PETRO STAR INC. WESTWARD SEAFOODS FUEL UPGRADE

Designed: RWM
Checked: RPH
Approved. TEH
Project No: 99205

P P

Peratrovich, Nottingham & Drage, Inc.

Engineering Consultants

RSA Engineering, Inc.

Date: 3/21/00 EL Scale: AS SHOWN &

ELECTRICAL SITE PLAN & DETAILS

E1 - 2

#### ELECTRICAL SPECIFICATIONS

SCOPE OF MORN - FURNISH AND INSTALL ALL MATERIAL AND MORNABLE ELECTRICAL SYSTEM AS INCREATED ON THE DRAWINGS AND IN THESE SYSTEMICATIONS.

STANDARDS, CODES AND RECIZIATIONS - COMPLY WITH THE LATEST ADDIFFED EDITION OF THE NATIONAL ELECTRICAL CODE, UNKFORM BIRLDING CODE MICLUSING ALL STATE AND LOCAL AMENDMENTS TO THESE CODES

Y'N COMPLIANCE - ALL COCOS MO EQUIPMENT WHICH THE CONTRACT AND MEMORITOR IS PEQUIPED TO PURCHASE UNDER THE CONTRACT AND MEMORITOR CONTRACT AND MEMORITOR CONTRACT STORM COMPLIANCE SOFTWARE CREATED CREATED, COMPLIER SOFTWARE SYSTEMS, COMPLIER SOFTWARE CUSTOM ASPLICATION PROCRAMMING, OR OTHER SUMLAR SYSTEMS/TECHNOLOGIES THAT CALCILLATE DATE OR TIME DATA. SHALL BE CERTIFIC YEAR 2000 COMPLIANT IN THAT THEY CORRECTLY AND WITHOUT FALURE, PROCESS DATE OR TIME CALL BEFORE, DURNIC AND BEYCHO ALGUST 31, 1999, INCLUDING LEAP YEARS.

DRAMINGS — THE DRAMINGS LATE DIMORRAMATIC, NOT NECESSARLY SHOWNED. A OFFSETS OR EXACT LOCATIONS OF PIXTURES, SEQUENCH, ETC. UNLESS SECONDALLY DIMENSIONED REVIEW THE DRAMINGS AND SECONDANDS FOR EQUIPMENT FURNISHED BY OTHER CRAFTS BUT INSTALLED BY ACCORDANDS MITH THIS SECTION. BRING OUESTICHMELE OR OBSCURE TIEMS, APPARENT CONFLICTS BETWEEN PLANS AND SECONDATIONS, CONFERNING COCES OR UTUTIES REGULATIONS TO THE ATTENTION OF THE ARCHITECT. COCES, ORIGINALISES REQULATIONS, MANUFACTURERS INSTRUCTIONS OR STANDARDS. THE PRESCIPCIONE WITH THE TARK MORE STRINGENT OR COMPULET WITH THE DRAWINGS AND SPECIFICATIONS.

RECORD DRAWNOS — WARK UP A CLEAN SET OF DRAWNOS AS THE WORK PROCRESSES TO SHOW THE DIMENSIONED LOCATION AND ROUTING OF ALL ELECTROOL WORK WHICH WILL BECOME PERMANENTLY CONCRUED SHOW ROTING OF WORK IN PREVALENTLY CONCRUED BLIND SPACES WITHIN THE BUILDING. SHOW COMPLETE ROUTING AND SIZING OF ANY SICHHOLAND REVISIONS TO THE SYSTEMS SHOWN.

WERKMADER - INSTALLATION OF ALL WORK SHALL BE MADE SO THAT ITS SEVERAL COMPONENT PARTS SHALL FUNCTION AS A WORMABLE SYSTEM COMPLETE WITH ALL ACCESSORIES INCRESSART FOR ITS DEPERATION ALL MATERIAL AND FOUNDMENT SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS HISTRACTICKES AND IN ACCORDANCE WITH NECA STANDARDS, MATERIALS AND EXHIPMENT SHALL BE NOW AND SHALL CONTORN WITH APPLICABLE MOUSTRY STANDARDS, MEAN STANDARDS AND UNDERWRITERS LABORATORIES STANDARDS WHERE APPLICABLE

SUBMITIALS - PROVICE MATERIAL AND EQUIPMENT SUBMITIALS CONTAINING A COMPLETE LISTING OF MATERIAL AND EQUIPMENT SHOWN ON THE DEADNINGS. INCLUDE CATALOG MANEERS, MIRTHO EDUCAMS, ROUGH-IN DIMENSIONS AND PERFORMANCE DATA FOR ALL MATERIAL AND FORMANT. SUBMITIALS SHALL BE BOUND IN HARD COVER, LOCSELER BINGERS SEPARATE FROW WORK FLANSHED UNDER OTHER CHASONS. INCEX AND CLEARLY DENTRY ALL MATERIAL AND CONTROL OF THE MALE OR DESONATION USED ON THE DENTRHOS. SUBMITIAL ROYER IS FOR CENTRAL DESON AND ARRANGEMENT ONLY AND DOES NOT RELIEVE THE CONTROL OF FROM ANY PROJUBELIEST OF THE CONTRACT DEQUIPMENTS. THE SUBMITIALS ARE NOT DESCRIBED FOR MATERIAL PROPERTY OF THE CONTRACT DEQUIPMENTS. THE SUBMITIALS ARE NOT DESCRIBED FOR MATERIAL PROPERTY OF THE PERFORMANCE HAVE NOT BEEN SPECIFICALLY NOTED IN THE SUBMITIAL BY THE CONTRACTOR, PROVISIONS OF A COMPLETE AND SARSACTIONS WORKING MISTALLADON IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR, PROVISIONS OF A COMPLETE AND SARSACTIONS WORKING MISTALLADON IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

CPCRATION AND MANTEMANCE MANUALS - PROVIDE OPERATION AND MANTEMANCE MANUALS FOR TRAINING OF THE OWNER'S PERSONNEL DESCRIBE THE PROCEDURES RECESSARY TO OPERATE THE STSTEM NEULUNG START-UP, OPERATION AND A SCHEDULE OF PREVENTIVE MANTEMANCE IN TABALAR FROM FOR ALL ROTTHE CLEMING, INSPECTION AND LUBRICATION WITH RECOMMENCE ULBRICAMTS, INSPECTION AND LUBRICATION WITH RECOMMENCE OF ADJUSTMENTS REQUIRED FOR PREVENTIVE MANTEMANCE ROUTINES. PROVIDE MANTEACTURER'S DESCRIPTIVE LITERATURE MICLIONIC APPROVED SHOP DEVINES USED IN ANY CONTRACTOR-PROVIDED EQUIPMENT OR SYSTEMS WITH RELUSTRATION, EXPLODED VESS, ETC.

WARRANTY - THE CONTRACTOR SHALL QUARANTEE ALL WORK EXECUTED UNDER THIS CONTRACT TO BE FREE FROW DEFECTS IN MATERIALS AND WORKMASHEP FOR A PERICO OF ONE YEAR FROW BENEFICIAL COCUPANCY ANY FALLY MATERIALS OR WERYLAWGUNG SHALL BE PERAMED OF REPLACED TO THE CANNER DURING THE GUARANTEE PERICO.

PERMITS - SECUPE AND PAYFOR ALL FEES, PERMITS, ETC.
REGURED BY LOCAL AND STATE ACENCIES AND ALL LOCAL LITERIT
COMPANIES. COSTS OF LINE EXTENSIONS TO THE WETER ARE TO BE
PAID BY THE OWNER.

REFERENCE STUBOLS - THE ELECTRICAL "LECENO" ON THE DRAWINGS IS A STANDARDIZED VERSION, AND ALL STUBOLS SHOWN MAY NOT BE USED. USE THE "LECENO" AS A REFERENCE FOR THE STUBOLS USED ON THE DRAWINGS.

IDENTIFICATION - PROMDE ENGRAVED THREE-LUTS LAMINATED PLASTIC NAMEPLATES WITH WHITE LETTERS ON A BLACK BACKGROUND TO IDENTIFY ALL ELECTRICAL DISTRIBUTION AND CONTROL EQUIPMENT, LOADS SERVED AND AS NOTED ON THE FRAMINGS. LETTER HEIGHTS SMALL BE 1/3 SHICH FOR INCOMOUN, SWITCHES, MOTED HEIGHTS SMALL BE 1/3 SHICH FOR INCOMOUN, SWITCHES, MOTED STATTERS, AND LOADS SERVED AND 1/4 WHICH ON PAWELEDARDS SECURE NAMEPLATES TO EDUPMENT FRONTS USING SCREWS, RIMITS OF ADMESSAGE SECURE NAMEPLATE TO INSIDE FACE OF RECESSED PAMELBOARDS DOORS OF PROMPOLO LOCATIONS.

COMMUNITS: MARK ALL COMMUNITS ENTERING OF LEAVING PANELBROADDS WITH INCELIBLE BLACK MACK MARKER WITH THE CIRCUIT HUMBERS OF THE CIRCUITS CONTAINED INSIDE.

JUNCTION BOXES MARK ALL CIRCUIT MUNBERS OF IMPRING ON ALL JUNCTION BOXES WITH SHEET STEEL COVERS. MARK WITH INCELIBLE BLACK MARKER.

CONDUIT - ALL WISHING SHALL BE INSTALLED IN METALLIC RACENAY.

RACENAY SHALL BE INSTALLED CONCEALED EXCEPT AT SURFACE

MOUNTED CHARLETS, MOTORS, AND ECUIPMENT CONNECTIONS. THE

RACENAY SYSTEM SHALL NOT BE USED AS THE EQUIPMENT CROUNDING

CONDUCTION PROVISE A SEPARATE CREEN CROUNDING CONDUCTION IN

ALL RACENAYS. UTILIZE CALVANATED RODD STEEL OR

MIERRACIONATS. UTILIZE CALVANATED RODD STEEL OR

MIERRACIONATE METAL CONQUET IN HOT LOCATIONS, IN DIRECT

CONTACT MITH. CONCRETE OR BELOW SURB ON CRUDE. ELECTRICAL

METALLIC TUBBINS MAY BE USED IN ALL CONCEALED, DRY, INTERPOR

LOCATIONS, UTILIZE SPORT EXTENSIONS (35 MODES MUNIMIA) OF

LOCATIONS. UTILIZE CONQUET FOR ALL MOTOR AND ECOUPMENT

CONMECTIONS. CONPLETELY AND THORROUGHY SWAB PACEMAY STSTEM

BEFORE INSTALLING CONCUCTORS.

CONDUCTORS - ALL CONDUCTORS SHALL BE COPPER WITH TYPE THEM, DMM, DHM OR THEM INSULATION. WINNAUM BRUNCH CROUT COMDUCTOR SIZE SHALL BE IZ AMC, HAMILIAM CONTROL CROUT CONDUCTORS SIZE SHALL BE JIB AMC, HALL ALL CHORUCTORS WITH THE RACEMAY AT THE SAME TIME, COLOR CODE CONDUCTORS AS FOLLOWS: 120/208 VOLI SYSTEMS: BLACK, RED, BLUE AMO WHITH USE PROPERTY SIZED MISULATED SHRING ME CONNICTORS WITH PLASTIC CAPS FOR ALL CONDUCTORS JIB AMC AND SAMLER. TERMINALE JIS AMC AND LARGE CONDUCTORS WITH CRUP OR COUPERSSOON THE CONNECTIONS WISTALED WITH FOOD RECOMMENDED BY CONNECTION MANUFACTURER AND INSULATE WITH PROPERTY SIZED 600 VOLI RAITED HEAT SHRINK TUBBER.

OUTLET BOXES - PROVIDE CALVANZED OR CADMRAI PLATED, ONE PIECE PRESSED STEEL OUTLET BOXES 4 MICH SOLURE OR OCTAGONAL 1 1/2 INCHES DEEP MINIMUM SIZE FOR USE IN MITEROR AREAS. PROVIDE CAST ALUMINAN OR FERRALLOY TIPSE BOXES WITH CADCRETO COVER, PHREADED MUSS, AND MEMA JR RAINNG FOR USE IN EXTEROR OR WET LOCATION, PROVIDE OUTLET BOXES AS SHOWN ON THE DIAWNOS, AND AS REQUIRED FOR SPLICES, TAPS, WIRE PULLING, EQUIPMENT COMMETCIONS, DEVICE INSTALLATION AND CODE COMPLIANCE. SUPPORT BOXES MODEPENDENTLY OF COMOUNT.

PANELBOARDS - PANELBOARDS ARE EXISTING, NEW CIRCUIT BREAKERS SHALL BE BOLTON HERMAL MACHET (FOR THE WITH COMON TAP HANDLE FOR ALL POLES PROYER HEY CIRCUIT BREAKERS TO MATCH EXISTING STITLE, MAMUFACTURER, AND AIC RATING.

EQUIPMENT CONNECTIONS - PROVIDE WIRHING AND CONNECTION OF EQUIPMENT REQUIRING ELECTRICAL POWER BUT SPECIFIED LINDER OFFICIAL OF THE SPECIFICATIONS. EQUIPMENT SHALL MICLIOE BUT IS NOT LIMITED TO PHILIP CONTROLS AND FUEL DISFENSER. REVIEW EQUIPMENT SUBMITIALS PRIOR TO INSTALLATION AND ELECTRICAL ROUGH-IN. VERBY LOCATION, SEEL, TIPE OF CONNECTIONS, AND THAT EQUIPMENT IS READY FOR ELECTRICAL CONNECTION, MAD THAT EQUIPMENT IS READY FOR ELECTRICAL CONNECTION, MAD THAT EQUIPMENT IS CONTROL. PARTIES OF PROVINCE CONTROL CONNECTION, MAD THAT EQUIPMENT IS CONTROL. PROVIDE WITH THE MANUFACTURER'S INSTRUCTIONS. PROVIDE MITERCONNECTION, WITHING AND DISCONNECTS WHERE REQUIRED.

DISCONNECT SWITCHES - PROVIDE UL LISTED 250V, HEAVY DUTY POSTELL GUICK-HAME, GUICK BERM, LOUD HIERROFFER, ENCLOSED KHIFE SHEER ERERNALT, OFFERVELL PANIEL BYTERLOCKED TO PREVENT OPENING FRONT COVER WITH SWITCH IN ON POSTON, HANDLE LOCKABLE IN OFF POSTION, MO FUSE CUTY LESSANGED TO ACCOMMODATE CLASS R PUSES AND REJECT ALL OTHER CLASS. FUSES.

are.

ENCLOSURES SHALL BE NEMA I OR 3R AS INDICATED ON THE CRAMINGS INSTALL ANSI/UL 1986 CLASS RNS 250 VOLT ONE-TIME PUSES, 200,000 RNS AMPERE INTERRUPTING RIFED OF SYZE INDICATED ON THE DRAWINGS IN ALL FUSIBLE DISCONNECT SWITCHES

SMITCHES

MOTOR STARTERS - PROMDE MACAETIC MOTOR STARTERS; NEMA ICS
2. AC GENERAL-PURPOSE CLASS A MACHETIC CONTROLLER FOR
INCICTION MOTORS RATED IN HORSEPOWER FULL VOLTACE
STARTING NON-REVERSING TIPE. OVERLOUN RELAY SHALL BE SOLID
START FIRE MITH J TO I ADJUSTION TO RELAY SHALL BE SOLID
PHASE LOSS AND UNBALLANCE PROTECTION. COMBINE MOTOR STARTERS
WITH FUSBLE SMITCH DISCONNECT IN COLUMN ENGAGER. PROMOSE
TWO FIELD COMPRETIBLE CONTACTS IN ADDITION TO SEAL-IN
CONTACT. PROMOSE MANHO/OFF/AUTO SELECTOR SMITCH AND A RED
"RUM" INDICATOR LICHT IN FRONT COVER, PROMOSE COMPINIOR
TRANSFORMERS AS REQUIRED. INSTALL MOTOR CONTROL EOUPEMENT
IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS. INSTALL
FUSES IN FUSBLE SMITCHES. SELECT AND INSTALL HEATER
ELEMENTS IN MOTOR STARTERS TO MATCH INSTALLE MOTOR
CHARACTERISTICS. MOTOR DATA PROMOSE MAINTY TIPED LUBEL
MISSOE EACH MOTOR STARTER BOLLOSURE DOES DONTPINE MOTOR
SERVED, MAMEPLATE HORSEPOWER, FULL LOAD AMPERES, CODE
LETTER, SERVICE FACTOR, AND VOLTACE/PHASE RATING.

PENETRATIONS - ALL ELECTRICAL PENETRATIONS THROUGH FIRE RATED BARRIERS SHALL BE SCALED IN ACCORDANCE WITH NEC ARTICLE JOD-71 AND THE FOLLOWING:

ALL HOLES OR VOIDS CREATED TO EXTEND LIFETRICAL SYSTEMS THROUGH FIRE REIDO RICORS AND WALLS SHALL BE SELED MITH ADDRESSED FIRE STOPPING MATERIAL CAPAGE OF EXPONENCE & TO 10 TMCS WHEN EXPOSED TO TEMPERATURES 250 OCCREES FOR MOHER.


MATERIALS SHALL BE SUITABLE FOR THE FIRE STOPPING OF PENETRADONS MUDE BY STEEL CLASS, PUSITIC AND SHALL BE CAPABLE OF MAINTAINING AN EFFECTIVE BURRIER ACASET FLAME, SUCRE AND GASES IN COMPLUNCE MITH THE RECONSTRUCTIONS OF ASTIM EBIL4, UL 1479 AND THE UL FIRE RESISTANCE DIRECTORY REQUIREMENTS FOR THROUGH-PENETRATION FIRESTOP DEVICES (YEAR).

THE RATING OF THE FIRE STOPS SHALL BE THE SAME AS THE TIME-RATED PLOCE, OR WALL ASSEMBLY

INSTALL FIRE STOPPING MATERIALS IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.

UNLESS PROTECTED FROM POSSIBLE LOADING OR TRAFFIC, INSTALL FIRE STOPPING MATERIALS IN FLOORS HAWNG VOID OPENINGS OF FOUR (4) INCHES OR MORE TO SUPPORT THE SAME FLOOR LOAD REQUIREMENTS AS THE SURROUNGHO FLOOR.


RACEMATS PENETRATING VAPOR BARRIERS OR PENETRATING AREAS FROM COLD TO WARM SHALL BE SEALED WITH A NON-HARDENING DUCT SEALON COMPOUND TO PREVENT THE ACCUMULATION OF MOSTURE, AND SHALL INCLUDE A VAPOR BARRIER ON THE OUTSIDE




1) PUMP CONTROL STATION SCHEMATIC

#### NOTES

 CONNECT TO HEM SOAJSP GROUT BREAKER IN EXISTING 120/2089, PANELBOARD IN EXISTING POWER HOUSE BUILDING, COORDINATE WITH OWNER FOR LOCATION, RUN IN TRENCH ALDING ROWD WITH FUEL PRING, COORDINATE WITH DWINER ON LOCATION TO RUN TRENCH ACROSS ROAD.





3 PUMP HOUSE POWER PLAN



# PETRO STAR INC. WESTWARD SEAFOODS FUEL UPGRADE

Designed: RPH
Checked RPH
Approved TEH

Project No. 99205

Peratrovich, Nottingham & Drage, Inc.

Engineering Consultants

1008 West 36th Arenus,
Anchorage, Alesta 89503 (1987) 861-1071 FAX (1907) 863-4220

RSA Engineering, Inc.

Dote: 3/21/00 Scale: AS SHOWN

ELECTRICAL SPECS POWER PLAN AND DETAILS

E2- 2